## Jet Range



- Ergonomic handle for a safer grip and to facilitate transportation
- IPX4 Protection Class
- All models have a 1.5 m H07 RNF power cable with Schuko plug, main witch and a pipe-hold er fitting with a diameter of 25 mm




- Hydraulic system in NORYL, single JET impeller to guarantee greater efficiency
- Suitable for clear water with a maximum temperature of 50°/35° C according to the model.
- Not suitable for sea and waste wateror for water containing corrosive or easily inflammable fluids



Flotec

- Single-phase, asynchronous electric motor with built-in thermal relay.
- Class F motor winding
- AISI 416 STAINLESS steel motor shaft
- Pump inlet and outlet with a diameter of 33,25 mm (1")






Article	N4176950	N4176650
Bar code	8010583529005	8010583124408
Input power	600 W	800 W
Max Head / pressure	43 m / 4,3 bar	46 m / 4,6 bar
Max flow rate	2700 l/h	3300 l/m
Voltage	230V 50 Hz	230V 50 Hz
Rated currents	3A	4A
Suction / delivery port	33.25 mm (1"F)	33.25 mm (1"M)
N° of impellers	1	1
Pump body	Cast Iron	Polypropylene (drinkable water)
Max advised suction depth	7m	7m
Accessories	Hose connector Ø 25 mm	Hose connector Ø 25 mm Suction kit 7 m
Ø Hose diameter 灣 N. irrigators m Lenght of the pipe	Ø 19 音音 音音 音音 25 音音 25 m 50 m 75 m 100 m	Ø 19 客音 音音 音音 25m 50m 75m 100m

## THE PUMP SPECIALIST





Article	N4176960		
Barcode	7630014507719		
Absorbed power	1100 W		
Max Head / pressure	50 m / 5 bar		
Flow rate	4800 l/h		
Voltage	230V 50 Hz		
Rated current	5A		
Suction / delivery port	33.25 mm (1"F)		
N° of impellers	1		
Pump body	Cast Iron		
Max advised suction depth	7m		
Accessories	Hose connector Ø 25 mm		
Ø Hose diameter 雲 N. irrigators m Lenght of the pipe	Ø 19 音音 音音 音音 25m 50m 75m 100m		









Article	N4176600	N41 77000
Barcode	8010583124378	7630014516216
Absorbed power	800 W	1200 W
Max Head / pressure	46 m / 4,6 bar	50 m / 5 bar
Flow rate	3300 l/m	4300 l/h
Voltage	230V 50 Hz	230V 50 Hz
Rated current	4A	5A
Suction / delivery port	33.25 mm (1"M)	33.25 mm (1"F)
N° of impellers	1	1
Pump body	Stainless steel	Stainless steel
Max advised suction depth	7m	7m
Accessories	Hose connector Ø 25 mm Suction hose 7 m	Hose connector Ø 25 mm Suction hose  7 m
Ø Hose diameter 灣 N. irrigators m Lenght of the pipe	Ø 19 25m 50m 75m 100m	Ø 19 常音 音音 音音 25m 50m 75m 100m

The number of irrigators has been calculated taking into account a flow rate of about 600 l/h and a pressure of 2 bar