

LOW VOLTAGE

SURFACE LOW VOLTAGE DIAPHRAGM PUMP

C

TMC-36501 4 chamber diaphragm design with a smooth constant flow. Can serve up to 3 to 4 outlets. Built in check valve to prevent back flow. Snap in inlet and outlet fittings ½” bsp and 13mm hose tails included. Built in thermal overload protection. Self priming and can be run dry. 1.4 bar cut in pressure and 2.8 bar cut off pressure. These are fixed and cannot be altered.



MODEL	VOLTAGE	INLET / OUTLET	LM/HM	AMP	H x W x L mm	Kg	CODE
TMC-36501	12v	½” or 13mm	16/28	15	97 x 90 x 235	4.6	020-910
TMC-36501	24v	½” or 13mm	16/28	8	97 x 90 x 235	4.6	020-915

SURFACE LOW VOLTAGE GEAR PUMP

C

Self priming bronze gear pump. Suitable for pumping diesel and light weight oils. Complete with inline fuse. Can prime (wet) from 2.5m. Recommended maximum oil thickness SAE 20W/50. Inline filter on the inlet with spare gauze.



MODEL	VOLTAGE	INLET / OUTLET	LM	AMP	H x W x L mm	Kg	CODE	PRICE
TMC-6010101	12v	15mm	4	15	171 x 183 x 161	4.6	3.8	020-900
TMC-6010101	24v	16mm	4	8	171 x 183 x 161	4.6	4.4	020-905